The red words are revised due to the 'Incorrect data for pressure at Primary Containment Vessel of Unit1 "which we announced on November 29.

Fukushima Daiichi Nuclear Power Station Plant Parameters

[Note]

Some indicators might not be functioning properly beyond the normal condition for usage affected by the earthquake and subsequent events. We comprehensively evaluate situation in plants using all the available information from indicators and also focusing on trends, taking uncertainty of indicators into consideration.

As of 6:00 am on May 24 Unit Unit 1 Unit 2 Unit 3 Unit 4 Unit 5 Unit 6 resh water feeding Fresh water feeding resh water feeding ₩2 Status of water Fire suppression system 3.1m³/h (5:00 am, 5/24) Feed water system 12.0m³/h (11:00 am, 5/23) (Heat removal of the reactor is functioning. Water eed water system 6.1m^3/h Fire suppression system 7.0m^3/h injection to the (as of 5:00 am, 5/24) (as of 5:00 am, 5/24) injection is unnecessary) reactor ⁻uel range A: Downscale Fuel range A:-1850mm Fuel range A:-1500 mm Stoppage range Stoppage range Water level in the -uel range B:-1600 mm Fuel range B:-2100 mm Fuel range B:-2250mm 1832mm 2206mm reactor (as of 5:00 am, 5/24) (as of 6:00 am, 5/24) (as of 6:00 am, 5/24) (as of 5:00 am, 5/24) (as of 5:00 am, 5/24) Syatem A:0.545 MPa g Syatem A:-0.018 MPa g Syatem A:-0.128 MPa g (A) (A) 🔆 3 (A) 💥 3 Pressure in the 0.007 MPa g 0.016 MPa g System B:1,475 MPa g Syatem B-0.113 MPa g (B) %3 Syatem B:-0.020 MPa g (D) %3 (C) 🔆 3 (as of 6:00 am, 5/24) (as of 6:00 am, 5/24) reactor (as of 5:00 am, 5/24) (as of 5:00 am, 5/24) (as of 5:00 am, 5/24) 46.4 ℃ 49.3 ℃ Water temperature of (as of 6:00 am, 5/24) (as of 6:00 am, 5/24) (Since there is no water inflow in the system it is impossible to collect the data) the reactor Temperature in feed-water nozzle 115.8 %3 Temperature in feed-water nozzle:112.3 Temperature in feed-water nozzle 106.6 X3 ×2 ×1 Temperature around (Monitoring is *2 (monitoring through water temperature of the react Temperature at reactor vessel Temperature at reactor vessel Temperature at reactor vessel the reactor vessel unnecessary bottom:1080 °C bottom:96.8 °C bottom:1001°C since all fuel are D/W:0.1010 MPa abs)/W:0.13<u>14 MPa abs*</u> D/W.0.040 MPa abs takeoff) Pressure in D/W · S/C:0.100 MPa abs S/C: Downscale ×1 S/C:0,1908 MPa abs S/C (as of 5:00 am, 5/24) (as of 5:00 am, 5/24) (as of 5:00 am, 5/24) RPV bellow seal: Overscale RPV bellow seal:97.6 °C RPV bellow seal:128.5 °C жз <u>×1</u> D/W Atmosphere HVH return:96.2 °C HVH return:111°C HVH return 105.9 °C temperature (as of 5:00 am, 5/24) (as of 5:00 am, 5/24) (as of 5:00 am, 5/24) %2 D/W(A):633E-01Sv/h D/W(A):7.79E+00Sv/h **%**1 D/W(A):1,77E+01Sv/h (Monitoring is unnecessary since heat removal of (B):3.05E+01Sv/h Ж1 (B):1.97E+01Sv/h (B):4.80E+00Sv/h reactor is functioning.) CAMS radiation S/C(A):3.09E-01Sv/h S/C(A):3.93E-01Sv/h S/C(A):9.74E-01Sv/h ЖЗ жз жз monitor жз жз жз (B):9.97E-01Sv/h (B):4.48E+01Sv/h (B):3,58E-01Sv/h (as of 5:00 am, 5/24) (as of 5:00 am, 5/24) (as of 5:00 am, 5/24) System A:53.6 °C System A:42.9 °C System A:64.4°C System B:53.4 °C System B:64.5°C System B:42.9 °C Temperature in S/C (as of 5:00 am, 5/24) (as of 5:00 am, 5/24) (as of 5:00 am, 5/24) Designed usable D/W 0.384MPa_g (0.485MPa_abs) 0.384MPa g (0.485MPa abs) 0.384MPa g (0.485MPa abs) pressure Designed usable D/W 0.427MPa g (0.528MPa abs) 0.427MPa g (0.528MPa abs) 0.427MPa g (0.528MPa abs) maximum pressure 42.5 ℃ Temperature in the 61℃ 62 °C 84 °C 31.0 ℃ Ж1 spent fuel pool (as of 5:00 pm 5/24) (as of May 8) : **4 (as of May 7) : **4 (as of 6:00 am, 5/24) (as of 6:00 am, 5/24) 6400mm FPC skimmer surge 2100mm 3650mm Ж1 (as of 5:00 am, ₩2 (as of 5:00 am, 5/24) (as of 5:00 am, 5/24) tank level 5/24) Receiving offsite power (P/C2C) Receiving offsite power (P/C4D) Receiving offsite power Power source Temperature in the Common Spent Fuel Regarding reactor water level fuel range A of Unit 1, inspection of the instrument was completed at 5:00 pm, May 11 5u: SHC mode 6u: Non-thermal mode Storage: Others Data of Pressure in D/W of Unit 1 on 11/29 was corrected because it was incorrect. 29°C (from 9:27 pm, 5/23) (from 5:23 pm, 5/23) (as of 6:30 am, 5/23) Pressure conversion Gauge pressure(MPa g) = Absolute pressure(MPa abs) - atmospheric pressure (normal atmospheric pressure(.1013 MPa) %1 ∶ Instrument failure Absolute pressure (MPa abs) = Gauge pressure (MPa g) + atmospheric pressure (normal atmospheric pressure0.1013 MPa) %2 : Not covered for colleting data

3 : continuously monitoring the status

※4 ∶ measured at SFP sampling

Fukushima Daiichi Nuclear Power Station Supplemental explanation for the plant parameters

■Supplemental explanation for each parameter

ltem	Recording manner	Measurement manner	Ch number or number of systems
Status of water injection to the reactor	Water inflow	Temporally	System 1 / 1
Water level in the reactors	Data measured by the water gauge, which monitor the fuel range	Main indicator	System A 1∕1Ch System B 1∕1Ch
Pressure in the reactor	Measure voltage value of pressure instrument by the main indicator panel and convert to the pressure. One representing value is noted among multiple data on each System A, B.	Measures voltage value through the main indicator panel and converts them to the pressure	System A 1/2Ch System B 1/2Ch
Temperature in the reactor	Since there is no water inflow at the points, where thermometers are set, no data is collected.	_	-
	Data measured at feed-water nozzle and at reactor vessel bottom are noted among multiple data to view the whole picture.	Main indicator	Point of Feed-water nozzle 1/4Ch reactor vessel bottom 1/2Ch (Unit1) 1/1Ch (Unit2/3)
Pressure in D/W • S/C	Data from main indicator. Measure voltage value by the main indicator panel converted to the pressure in case main indicator are not in function. (D/W : Dry Well、S/C : Suppression Chamber)	Unit1/2:Main indicator Unit 3:Main indicator panel (converted from voltage) :	Main indicator system 1 / 1 Main recorder regular use 1 / 1Ch wide range 1 / 1Ch
D/W Atmosphere temperature	Data at upper point (RPV Bellows Air) and middle point (HVH return) are noted among multiple data to view the whole picture. (RPV : Reactor Pressure Vessel、HVH : Heating Ventilating Handling Unit)	Main recorder	RPV Bellows Air 1 / 5Ch D/W HVH return 1 / 5Ch
monitor	Data from the instrument reading of main indicator. (CAMS : Containment Atmospheric Monitoring System)	Main indicator	D/W System A 1 / 1 Ch System B 1 / 1 Ch S/C System A 1 / 1 Ch System B 1 / 1 Ch
Temperature in S/C	Data from the instrument reading of main recorder. One representing value is noted among multiple data on each System A, B.	Main recorder	System A1/4Ch (Unit 1)、8Ch (Unit 2/3) System B1/4Ch (Unit 1)、8Ch (Unit 2/3)
Temperature in the spent fuel pool	Data from the instrument reading of main recorder (Non-thermal mode:Urgent Heat load Mode、SHC mode:Shut down Cooling Mode)	Main recorder	1/2Ch (Unit 1)、1Ch (Unit 2~4)
FPC skimmer surge tank level	Data from the instrument reading of main indicator (FPC : Fuel Pool Cooling and Filtering System)	Main indicator	System 1 / 1

■Supplemental explanation for notes

ltem	Contents	Status As of 6:00 am , 5/24
Instrument failure	Instrument failure : down of instrument reading (over) scale/failure of instrument	 Unit 1 Spent fuel pool temperature, CAMS D/W radiation monitor Unit 2 Temperature at reactor vessel bottom, pressure in S/C, RPV Bellows Air temperature Unit 3 Spent fuel pool temperature, level of skimmer surge tanks Unit 4 Spent fuel pool temperature
	Unit4: Monitoring is not implemented since all fuel are takeoff. Unit5/6: Monitoring is not implemented since heat removal of reactor is functioning	
Continuously monitoring the status	Inaccurate Data defined from relation with other Parameters such as negative figure.	 Unit 1 Reactor pressure, feed-water nozzle temperature, CAMS S/C radiation monitor Unit 2 Reactor pressure, CAMS S/C radiation monitor Unit 3 Reactor pressure, RPV bellow air temperature, feed-water nozzle temperature, CAMS S/C radiation monitor